

# Easy UPS 3L 400kVA 400V 3:3 UPS, Startup 5x8

E3LUPS400KHS

#### Overview

Presentation	Easy-to-configure, easy-to-use and easy-to-service 400 kVA 3 phase UPS with an exceptional combination of competitive specifications, compact footprint, and highly available parallel and redundant designs. The EcoStruxure connected Schneider Electric Easy UPS 3L is the easy choice for business continuity on your shop floor or in your electrical room. Includes 5x8 start-up service.
Lead time	Special Order - Call for Quoted Lead Times

#### Main

Mairi		
Main Input Voltage	400 V 3 phases	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	380 V 415 V	
Main Output Voltage	400 V 3 phases	
Other Output Voltage	380 V 415 V	
Rated power in W	400 kW	
Rated power in VA	400 kVA	
Provided equipment	Dust filter Installation manual Start-up service	
Range of product	Easy UPS 3L	

#### **Batteries & Runtime**

Efficiency	View Efficiency Graph ☐	
Battery type	External battery system	
Battery voltage	+/- 216+/- 300 V	
Maximum short-circuit current	35 kA	
Discharge battery voltage	+/- 172.8+/- 240 V	

# **Physical**

Colour	White (RAL 9003)	
Height	197 cm	
Width	60 cm	
Depth	85 cm	
Product weight	538 kg	
USB compatible	Yes	

## Input

Maximum input current	719 A	
Max short time withstand current	35 kA	
Input harmonic distortion	Less than 3 % for full load	
Load power factor	0.5 leading to 0.5 lagging without derating	
Input voltage limits	323477 V	
Network frequency	4070 Hz	

## **Output**

Maximum configurable power in VA	400 kVA	
Maximum configurable power in W	400 kW	
Output frequency	50 Hz sync to mains 60 Hz sync to mains	
Output harmonic distortion	< 2% linear load and < 4% non-linear load	
Output overload operation	10 minutes at 125% and 60 seconds at 150%	
UPS type	Double conversion online	

## Conformance

Product certifications	CE EAC
	RCM

## **Environmental**

Ambient air temperature for operation	030 °C	
Relative humidity	095 % non-condensing	
Operating altitude	04921 ft	
Ambient air temperature for storage	-2555 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	0.00000000014999.8 m	
Acoustic level	70 dB	
Heat dissipation	79181 Btu/h	
IP degree of protection	IP20	

# **Communications & Management**

control panel	Touch screen LCD user interface
---------------	---------------------------------

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2117 mm
Package 1 Width	1000 mm
Package 1 Length	800 mm
Package 1 Weight	584 kg

# **Contractual warranty**

Warranty

09-Jun-2025

1 year on-site repair or replace with factory authorized Start-Up



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	512737	

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
REACh Regulation	REACh Declaration

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

Image of product / Alternate images

#### **Alternative**



